

Technical Datasheet

E-A-R™ UltraFit™ Earplugs



Product Description

The E-A-R™ UltraFit™ pre-moulded earplugs are designed for insertion into the ear canal to help reduce exposure to hazardous levels of noise and loud sound. These products are available in corded and uncorded version.

Key Features

- Unique patented tri-flange design
- Longer stem helps make insertion easier
- Made from soft and durable material
- One size fits majority wearers
- High attenuation (SNR 32dB) amongst standard pre-moulded earplugs
- Compatible with E-A-Rfit validation system
- Easy to wash and clean
- Supplied in re-sealable pillow-pack for ease of use
- Available in both corded and uncorded version

Applications

The E-A-R™ UltraFit™ earplugs are ideal for high to moderate noise exposure levels, and are ideally suited for all frequency noise in a wide range of industrial workplace and leisure environment. Examples of typical applications include:

- Automotive
- Chemical & pharmaceutical manufacture
- Construction
- Heavy engineering
- Metal processing
- Textile manufacture
- Woodworking

Standard & Approval

The E-A-R™ UltraFit™ pre-formed earplugs are tested and CE approved against the European Standard EN352-2:1993. These products meet the Basic Safety Requirements as laid out in Annex II of the European Community Directive 89/686/EEC and have been examined at the design stage by INSPEC International Limited, 56 Leslie Hough Way, Salford, Greater Manchester M6 6AJ, UK (Notified Body number 0194).

Materials

The following materials are used in the manufacture of this product.

Component	Material
Earplugs	Thermoplastic elastomer
Cord	PVC



Attenuation values

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	29.2	29.4	29.4	32.2	32.3	36.1	44.3	44.8
sf (dB)	6.0	7.4	6.6	5.3	5.0	3.2	6.0	6.4
APVf (dB)	23.2	22.0	22.7	26.9	27.3	32.8	38.3	38.4

SNR = 32dB H = 33dB M = 28dB L = 25dB

Key

APVf (dB) = Mf – sf (dB)

Mf = Mean attenuation value

sf = Standard deviation

APVf = Assumed Protection Value

H = High-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = -2dB)

M = Medium-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = +2dB)

L = Low-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = +10dB)

SNR = Single Number Rating (the value that is subtracted from the measured C-weighted sound pressure level, L(C) in order to estimate the effective A-weighted sound pressure level inside the ear).

Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Occupational Health & Safety
Products EMEA Division
3M Svenska AB
Mammstengsgatan 19
331 02 Värnamo Sweden
Visit us: www.3M.eu/OccSafety

Secondary address
3M Operating Unit
Address
City, State, Postal Code
Country
Phone
Fax
Email

Website address
Please recycle.
© 3M 2009. All rights reserved.

Please recycle.
© 3M 2009. All rights reserved.



Need help? Contact us:
+44 (0)1604 468100
mail@itarus.com
www.itarus.com

Job Number: 118253

Date: 26/10/2009

AUIC: aSepip

Version: 4

1

Cyan

2

Magenta

3

Yellow

4

Black

